

ETA CE ETA-08/0007 D N Aluzinc						
VRFH Code	Ø tányér Ø plate	tányér anyagvastagság plate thickness	Furatátmérő Hole	✉		
DVP-EF-51N	51 mm	0,84 mm	6,70 mm	1000	DVP-EF-51N	
DVP-EFB-51NS	51 mm	0,84 mm	5,40 mm	1000	DVP-EFB-51NS	
DVP-EF-4010N	40 mm	1,0 mm	6,00 mm	1000	DVP-EF-4010N	
DVP-EF-5010N	50 mm	1,0 mm	6,30 mm	1000	DVP-EF-5010N	
DVP-EF-5010D	50 mm	1,0 mm	6,30 mm	1000	DVP-EF-5010D	
DVP-EF-8040N	80 x 40 mm	1,0 mm	6,50 mm	500	DVP-EF-8040N	
DVP-EF-8040D	80 x 40 mm	1,0 mm	6,50 mm	500	DVP-EF-8040D	
DVP-DF-8240H	82 x 40 mm	1,0 mm	7,00 mm	80	DVP-DF-8240H	
DVP-EF8240XH	82 x 40 mm	1,0 mm	4,85 mm	90	DVP-EF8240XH	
DVP-DF8240XH	82 x 40 mm	1,0 mm	7,00 mm	90	DVP-DF8240XH	
EDF-BAR-F	2250 x 30 mm	1,0 mm	4,85/8,00 mm	10	EDF-BAR-F: Eurofast Bar	
EDF-BAR-FB	2250 x 30 mm	1,0 mm	4,85/8,00 mm	10	EDF-BAR-FB: Eurofast Bar	
Műszaki adatok						
Fém tartótányérok: "EF" márkajelzéssel. Bevonat: Aluzinc 15 ciklusú Kesternich teszt szerint DIN 50018 S2,0L			DVP-EFB-51NS (FM-Approval)			
Technical details						
Steel decking plates, with EF-headmark Coating: Aluzinc 15-cycles of the Kesternich test acc. DIN 50018 S2,0L			DVP-EFB-51NS (FM-Approval)			
Technische Daten						
Metall Halteteller mit EF-Markierung Beschichtung: Aluzinc 15 Zyklen Kesternich Test nach DIN 50018 S2,0L			DVP-EFB-51NS (FM-Approval)			
Fiche technique						
Plaquette de répartition métallique, marqué EF Revêtement: Aluzinc 15-cycles Kesternich suivant DIN 50018 S2,0L			DVP-EFB-51NS (FM-Approval)			

